

DuoCrossPointer3 HP

The flexible



- » Combined cross and point laser
- Two laser crosses or 3 points
- Very long vertical line from floor to ceiling



1 Keypad

2 Universal mount

TECHNICAL DATA	DUOCROSSPOINTER3 HP	FEATURES	SUPPLIED WITH
			ART.-NO. 531000
Self-levelling range	± 4°	<ul style="list-style-type: none"> 2 laser crosses Very long vertical line from floor to ceiling (above zenith) Plumbing function Multi-functional mount Strong magnets on the bottom and back side with rubber pads Strap attachment Rotatable Self-levelling function can be switched off for manual use 3 laser dots: front, ceiling, floor 	<ul style="list-style-type: none"> Laser glasses Magnetic target Set of batteries Container
Accuracy	± 3 mm / 10 m		
Line laser function	2 laser crosses: front and ceiling		
Working range	20 m*		
Sector angle Hz-lines	110°		
Sector angle V-line	160°		
Point laser function	3 laser dots: up, down, front		
Working range	50 m		
Power supply	3 x AA Alkaline		
Operating time	7 h		
Dust / water protection	IP 54		
Laser diode / Laser class	635 nm / 2		
Temperature range	-10 °C – +45 °C		
Size	134 x 62 x 122,5 mm		

* depending on room illumination