

# Geo6X SP & Geo6X SP KIT

## 3 x 360° in red

Selection PRO



» Multi-functional for versatile levelling jobs at indoor construction sites.

» Simple outfit with alkaline batteries and bag



### FEATURES GEO6X SP

- 3 x 360°-laser lines form 6 laser crosses
- Laser lines switchable separately
- Plumbing function
- Laser plane distance to wall/ceiling min. 12 mm
- Magnets at the front and side for connection to dry wall track
- Use with receiver (optional)
- Self-levelling function can be locked for manual use
- 5/8" & 1/4" connection at the instruments bottom

### ADDITIONAL WITH GEO6X SP KIT UND GREEN KIT


- Multi-functional mount
- magnets on the back
- strap attachment
- height adjustable
- 5/8" tripod connection

Multi-functional mount **1**

Battery compartment **2**

| TECHNICAL DATA                       | GEO6X SP        | GEO6X SP KIT    | GEO6X SP GREEN KIT |
|--------------------------------------|-----------------|-----------------|--------------------|
| Self-levelling range                 | ± 3°            | ± 3°            | ± 3°               |
| Accuracy                             | ± 2 mm / 10 m   | ± 2 mm / 10 m   | ± 2 mm / 10 m      |
| Laser diode / class                  | red / 2         | red / 2         | green / 2          |
| Working range* (radius)              | 30 m            | 30 m            | 40 m               |
| Working range with receiver (radius) | 60 m            | 60 m            | 70 m               |
| Operating time / power supply        |                 |                 |                    |
| 1 x 360°                             | 16 h / alkaline | 20 h / Li-Ion   | 14 h / Li-Ion      |
| 2 x 360°                             | 8 h / alkaline  | 12 h / Li-Ion   | 7 h / Li-Ion       |
| 3 x 360°                             | 5 h / alkaline  | 8 h / Li-Ion    | 5 h / Li-Ion       |
| Dust / water protection              | IP 54           | IP 54           | IP 54              |
| Temperature range                    | -10 °C – +45 °C | -10 °C – +45 °C | -10 °C – +45 °C    |
| Size                                 | 14 x 13 x 8 cm  | 14 x 13 x 8 cm  | 14 x 13 x 8 cm     |
| Weight (instrument with battery)     | 0,8 kg          | 0,8 kg          | 0,8 kg             |

\*depending on room illumination



### SUPPLIED WITH GEO6X SP

ART-NO. 534000

- 4 x Alkaline batteries
- Magnetic target
- Softbag

### SUPPLIED WITH GEO6X SP KIT

ART-NO. 534100


- Multi-functional mount
- Li-Ion battery, charger
- Charger with USB 3.0 cable
- Magnetic target
- Battery case for alkaline batteries
- Container

# Geo6X SP GREEN KIT

## Like red, even better in green

» **Multi-functional for versatile levelling jobs at indoor construction sites.**

» Full kit with Li-Ion batteries, charger, wallmount, container, offering the benefits of an innovative tool for the professional user.



### SUPPLIED WITH GEO6X SP GREEN KIT

ART-NO. 534500

- Multi-functional mount
- Li-ion battery, charger
- Charger with USB 3.0 cable
- Magnetic target
- Battery case for alkaline batteries
- Container

### OPTIONAL

ART-NO. 500520

- Receiver FR 55-M  
**page 66**

ART-NO. 500510

- Receiver FR 55  
**page 66**

ART-NO. 290560

- Walltrack Adapter WS 1  
**page 116**