

Description

PU

Order No.
(EAN-Code)

Accessories



RangeXtender RX 51

Laser receiver for all line lasers with RX-READY technology. With RX-READY, the laser lines pulsate at a high frequency (10 kHz). This pulsation allows the range extender to detect laser lines up to a maximum of 50 m away. The universal mount enables the device to be attached to levelling staffs.

Incl.: universal mount and battery

1

033.20-1



PT



Commander 50

Infrared remote control for Titanium, DuraMax, ACM, AQM and BCM rotary lasers, range up to 50 m.

1

045.50



IQ



SensoLite 120 Set

Laser receiver for rotary lasers, laser reception range 120 m for red and green lasers, with head magnet. High-luminosity LEDs on front and rear. SpotLite function. **Incl.:** universal mount

1

026.50



PT



SensoLite 310 Set

Laser receiver for rotary lasers, one LCD on the front and one on the rear, five-digit display, various acoustic melodies support the optical indicators, extremely loud piezo buzz tone possible, SpotLite function, head and side magnets, reception range 300 m for red lasers, 200 m for green lasers, extremely durable design. **Incl.:** universal mount

1

028.71



IQ



SensoCommander 120 Set

Combined laser receiver and infrared remote control for Titanium, DuraMax, ACM, AQM and BCM rotary lasers, reception range 120 m for red lasers, with head magnet, high-luminosity LEDs on the front and rear, SpotLite function, IR remote control range 15 m. **Incl.** universal mount. Not suitable for green lasers.

1

026.01.00



PT



SensoCommander 310 Set

Combined laser receiver and infrared remote control for Titanium, DuraMax, ACM, AQM and BCM rotary lasers, reception range 300 m for red lasers, one LCD on the front and one on the rear, five-digit display, various acoustic melodies support the optical indicators, extremely loud piezo buzz tone possible, SpotLite function, head and side magnets, IR remote control range 15 m. **Incl.** universal mount. Not suitable for green lasers.

1

028.70



IQ



SensoMaster 400 Set

High performance laser receiver in extreme robust quality for red lasers with a laser receiver area of 127 mm length for a distance over 300 m. The difference of height in reference to the laser plain is shown by LC-Displays on front and back either numerically or in arrow diagrams. The numerical value shows the exact distance to the laser plain, the arrow diagrams go proportionally either up or down. Three bright LED's on the front plus, if desired, an extreme loud piezo sound show the height in relationship to the laser plain. Designed for tough construction and outdoor environments, water- and dustproof according to IP 67, special rubber protection. **Incl.** universal mount. Not suitable for green lasers.

1

028.80



IQ



K

Description

PU

Order No.
(EAN-Code)

Accessories



SensoPilot Pro

Machine laser receiver for construction machine control. In combination with a rotary laser, the SensoPilot serves as a continuous guide for height control. Each of its four laser receiver units, which measure 25 cm in length, can receive the laser beam in a 360° radius. Large clearly visible LEDs show the laser's level. Range 200 m. Highly durable waterproof and dust-proof housing with powerful magnets to fasten the device to the machine. Not suitable for green lasers.

Incl.: built-in battery, charger, 12/24 V battery cable and case

1

035.00A



IQ



IP 66



Remote Display for SensoPilot

This remote display allows reference height to be monitored from the driver's seat of the construction machine. This is the ideal complement for the SensoPilot mobile laser receiver. Very robust design with mounting socket, water and dust-proof housing.

Incl.: Connection cable for SensoPilot.

1

035.01



IQ



Mounting Brackets

for SensoPilot (2 pcs.)

1

035.02



IQ



PowerPack Fast

High-quality charger including 4 high-performance batteries, type AA. Includes adapters for Europe, UK, Australia and USA.



100V – 240V AC



Adapters



12V DC

1

039.901A



IQ

NEW



MultiNorm Mains Connection Unit

fu'r AutoLite-Laser Green, AQM, AquaPro, AQM Pro 120, BCM Basic-Plus, ACL 4 P.
Inklusive Adapter fu'r Europa, England, Australien und USA.
6 V, 300 mA.


1

050.82-3



Magnetic target plate

With adhesion magnets and dual scale, for all laser spirit levels, e.g. for lowering ceilings, or with Flexi staff.



1

023.61A



PT



Magnetic target plate green

with adhesion magnets and dual scale, for all rotary lasers or laser spirit levels, e.g. for lowering ceilings.



1

023.65



IQ



Laser Enhancement Glasses Green

for optimum visibility of the laser marker from distance. Please make sure these are always used in outdoor applications involving green laser instruments.

1

020.71



IQ