

Interior finishing and building



RangeXtender 51



Laser receiver for all line lasers with RX-READY technology

- Fast alignment work in close and long range
- With RX-READY, the laser lines pulsate at a high frequency. This pulsation allows the range extender to detect laser lines up to a maximum of 50 m away.
- The universal mount enables the device to be attached to levelling staffs.

Optional: softbag

Not suitable for green lasers.

Inclusive: universal mount, battery

ORDER NO.	EAN-CODE	PU
RX 51	033.20-1 4 021563 662920	1
Softbag	033.21 4 021563 663859	1



RangeXtender 52
TwinLevel



Laser receiver for all line lasers with RX-READY technology

- Two different sensitivity levels in close and long range
- With RX-READY, the laser lines pulsate at a high frequency. This pulsation allows the range extender to detect laser lines up to a maximum of 50 m away.
- The universal mount enables the device to be attached to levelling staffs.

Optional: softbag

Not suitable for green lasers.

Inclusive: universal mount, battery

ORDER NO.	EAN-CODE	PU
RX 52	033.20-2 4 021563 670895	1
Softbag	033.21 4 021563 663859	1




Magnetic target plate
red / green



For all rotary lasers or laser instruments

- With adhesion magnets and dual scale
- e.g. for lowering ceilings



ORDER NO.	EAN-CODE	
023.61A	4 011879 643980	red
023.65	4 021563 663439	green



Laser enhancement
glasses red / green



Optimum visibility of the laser marker from distance



- Please make sure these are always used in outdoor applications involving green laser instruments.

ORDER NO.	EAN-CODE	
020.70A	4 011879 644000	red
020.71	4 021563 663446	green





Revolution 310 S



- Fully automatic rotary laser**
- 4° self-levelling range, accuracy 0,75 mm / 10 m
 - Laser modes: spot, scan, rotary and hand receiver mode
 - Single-slope function for manual tilt of an axis in automatic operation, even if ADS tilt is active.
 - All functions can be controlled remotely using the Commander 50.
 - Laser receiver range up to 300 m radius

Inclusive: Revolution, SensoLite 310, universal mount, Commander 50, rechargeable battery, charger, battery holder, carrying case, batteries

ORDER NO.	EAN-CODE	PU
052.00.07A	4 021563 668557	1

Optional: Systainer® version, Page 83



SensoLite 120 set



- Laser receiver for rotary lasers**
- Laser reception range 120 m for red and green lasers
 - With head magnet
 - High-luminosity LEDs on front and rear

Inclusive: universal mount, battery

ORDER NO.	EAN-CODE	PU
026.50	4 021563 662845	1



SensoLite 310 set



- Laser receiver for rotary lasers**
- One LCD on the front and one on the rear
 - five-digit display, various acoustic melodies support the optical indicators
 - Extremely loud piezo buzz tone possible
 - Head and side magnets
 - Reception range 300 m for red lasers
 - 200 m for green lasers
 - Extremely durable design

Inclusive: universal mount, battery

ORDER NO.	EAN-CODE	PU
028.71	4 021563 663262	1



Above and below ground construction



SensoLite 410 Set


NEW



High-performance laser receiver with extremely large receiving range for red and green rotary lasers

- Extremely long laser reception range for quick laser acquisition at great distances
- LC displays at front and rear. Melodies indicate the level of the laser beam.
- At the front there are extremely bright 3-colour LEDs for remote identification as well as an optionally available extremely loud piezo-buzzer
- With improved universal holder
- Strong head and side magnets
- Circular bubble level
- Receiving range for red laser up to 400 m
- Receiving range for green laser up to 200 m

Available in July 2011.



Super bright signal LED: High, Low, Target

Inclusive: universal mount, battery

ORDER NO.	EAN-CODE	PU
028.75	4 021563 677214	1



SensoMaster 400 set



High performance laser receiver for rotary lasers

- 127 mm long laser receiver unit
- Millimetre exact distance reading for laser level
- Height difference to laser level is indicated by the double-sided LC display.
- Three bright LED's on the front plus, if desired, an extreme loud piezo sound show the height in relationship to the laser plane.
- Has a special protective rubber case
- Receiving range for red laser up to 400 m

Not suitable for green lasers.



With SenoLite 410 and SensoMaster 400 laser receivers the laser range is up to 400 m.

Inclusive: universal mount, battery

ORDER NO.	EAN-CODE	PU
028.80	4 021563 663934	1

