


Above and below ground construction



DualAxis Laser



IQ

2-axis grade laser of extremely durable design for civil and construction engineering

- 5° self-levelling range, accuracy 0.5 mm / 10 m
- Shutter function: The working range of the laser beam can be limited to 4 different segments.
- Deviation from the horizontal plane can set digitally in X and Y axes.
- Laser modes: rotary and hand receiver mode
- High maximum speed of 1100 rpm
- The telescopic sight supplied with the device makes alignment easy
- Large illuminated LCD
- All functions can be controlled remotely using the Commander DAL.

Accessories included:

universal mount, Commander DAL, telescopic sight, rechargeable batteries, charger, carrying case, batteries



Telescopic sight for adjusting the DualAxis-Laser

The telescopic sight ensures precision adjustment of the DualAxis-Laser X and Y axes. Simple 90° rotation facilitated by magnetic fastening.

Set DuralAxis 410 S

up to 400 mm with SensoLite 410 laser receiver

ORDER NO.	EAN-CODE	PU
043.00.09A	4 021563 677788	1

043.00.09A	4 021563 677788	1
------------	-----------------	---



Set DualAxis Laser 400 S

up to 400 m with SensoMaster 400 laser receiver
- 127 mm long laser receiver unit
- Highly accurate distance reading for laser level

ORDER NO.	EAN-CODE	PU
043.00.10A	4 021563 665709	1

