

Laser and levelling device accessories

Telescopic Stand 330 cm



High-quality aluminium telescopic stand, ideal for quick changes in applications where working positions vary

- The stand is clamped between floor and ceiling then the laser measuring tool is turned manually to set it to the correct height ready for operation.
- 5-piece design for easy transport
- Height approx. 330 cm



Inclusive: softbag

ORDER NO.	EAN-CODE	PU
090.120A	4 021563 665372	1




PT



Telescopic adapter

NEW



Adapter for telescopic stand 330 cm

- For retrofitting and multiple use of laser measuring instruments on telescopic stand.
- With additional 1/4" thread

For all laser measuring instruments



ORDER NO.	EAN-CODE	PU
090.120.1	4 021563 661084	1




PT

MiniStand 1/4"



Mini-tripod made of aluminium

- for LRM pocket, SCL 2, SCL 3 etc.
- 1/4" tripod connection
- Ball joint
- Telescoping tripod legs



ORDER NO.	EAN-CODE	PU
090.130A	4 021563 670550	1



PT

FlexPod


NEW



Nylon thermoplastic mini stand for LRM Pocket, LRM Pocket Pro etc.

- 1/4" tripod connection
- Ball joint and clamping screw for stepless adjustment
- With Velcro fastener for securing to shafts, extruded sections and roof laths
- Tripod feet with non-slip rubber caps
- Extendable

Available in April 2011.



ORDER NO.	EAN-CODE	PU
090.131A	4 021563 677245	1



PT

Wall Mount



For all Laserliner rotary- and linelasers

- With height adjustment and clamp bracket for attachment to construction elements.



ORDER NO.	EAN-CODE	PU
080.70	4 011879 631178	1



PT

Wall Mount Pro



For all Laserliner rotary- and linelasers

- With positioning wheel for precise height adjustment, clamp holder for attachment to structural elements.



ORDER NO.	EAN-CODE	PU
080.71	4 021563 658817	1



IQ

Laser and levelling device accessories

Angle Bracket 5/8"

Professional design with angle scale
 – Suitable for all laser measuring tools



ORDER NO.	EAN-CODE	PU
080.75	4 021563 662821	1



TelePilot 5 m

Professional telescopic measure with window
 – Allows even great heights to be read with accuracy
 – Guided, inside steel tape measure
 – For inside and outside measurement
 – With lock for each individual section



ORDER NO.	EAN-CODE	PU
075.105	4 011879 635398	1



A comprehensive assortment of levelling staffs to cover the most diverse of applications. Particularly well suited for measuring ground levels or interior/exterior measurements. Suitable for use with automatic levelling and laser measuring instruments.

Flexi Levelling Staff

For all measurement of floor height
 – Reference height approx. 80-190 cm ± 50 cm measurement range, max. length approx. 240 cm
 – Height difference can be read off directly with no calculation necessary
 – Unmatched by any normal levelling staff



Flexi levelling staff red
 – Ideal for red lasers

Flexi levelling staff green
 – Ideal for green lasers

	ORDER NO.	EAN-CODE	PU
red	080.50	4 011879 631147	1
green	080.51	4 021563 664948	1



Flexi-Slider

Optimum positioning aid for laser receiver at Flexi levelling staff
 – Smooth slider for quick and easy use
 – With quick-action clamp



UNLIMITED MOVE

ORDER NO.	EAN-CODE	PU
080.52	4 021563 673292	1



Telescopic Levelling Staff

Easily legible, highly stable levelling staffs for use even under extreme conditions
 – Made of strong aluminium section
 – For optical levels and rotary lasers
 – Telescopic Levelling Staff 4 m: max. height 4 m, min. height 1.19 m
 – Telescopic Levelling Staff 5 m: max. height 5 m, min. height 1.22 m



ORDER NO.	EAN-CODE	
080.40	4 011879 630966	4 m
080.41	4 011879 630973	5 m

