



NEW!



MSLEK Momentum: Single Laser Exterior Kit

Visible laserchalkline, single diode solid-state rotary laser. Both horizontal or vertical plane projection. Fine pitch manual levelling screws. Alloy levelling base with 1/4in and 5/8in threads for tripod or laserslide mounting. Laser receiver provides visual and audio indicators with auto shut-off feature.

Range 30m, or 120m radius with laser receiver

Laser diode 635nm Class 3A < 5mW

Accuracy $\pm 2.0\text{mm}/10\text{m}$

Rotation speed 0-600rpm

Power 6 x AA batteries included

Duration 24 hours approx

Kit complete with laser receiver, staff clamp, instruction manual and carrying case.



MDLCK Momentum: Dual Laser Ceiling Kit

Special model for suspended ceiling installation. Highly visible, laserchalkline. Patented dual diode solid-state rotary laser. Both horizontal or vertical plane projection. Fine pitch manual levelling screws. Alloy levelling base with 1/4in and 5/8in threads for tripod or laserslide mounting. Adjustable ceiling bracket.

Range 40m



Laser diodes 2 x 635nm Class 3A < 5mW.

Accuracy $\pm 2\text{mm}/10\text{m}$.

Rotation speed 0-600rpm.

Power 6 x AA batteries included.

Kit complete with ceiling bracket, magnetic target, laser enhancement glasses, instruction manual and carrying case.



Accessories

MCT Mini Crank Tripod

Robust alloy construction with adjustable legs and centre column. Height 0.57m - 1.22m, includes 150mm column extension with 5/8in thread.

RT Reflective Target

For height measurement in combination with Flexi Levelling Staff. Dual scale with staff clamp.

FLS Flexi Levelling Staff

Alloy tubes, graduated in mm, with lower section adjustable in height for zero setting at datum. Fitted with circular vial. Reference height approx 0.8m to 1.9m $\pm 500\text{mm}$ measurement range. Max height 2.4m.

LSP LaserSlide Pro 3.3m

Alternative to a tripod for interior work. Small footprint support pole in 5-sections with twist grip telescopic adjustment. Height range up to 3.3m - floor to door jamb or ceiling. Quick-action adjustable platform with 1/4in and 5/8in threads.