

Laserliner®

AquaPro Laser 120 Set

Automatic rotary laser with laser receiver, stand and levelling staff.

Rev.1.209

AquaPro 120

- **Automatic level:** Automatic rotary laser with horizontal self-levelling by means of magnetically damped pendulum system; vertical alignment with adjustable foot.
- A **vertical reference beam** is provided to plumb and align partition walls.
- Robust housing with **protective rubber casing**.
- **Out-of-level:** The device emits visual and acoustic signals to indicate that it is out of the levelling range.
- **Laser modes:** Rotary and hand receiver mode.
- **Inclination** can be set.
- **SpotLite marking function:** Prevents parallax errors and facilitates precise marking of reference levels.
- The **wall/floor console** can be vertically levelled or the unit can be attached to the wall.
- Pendulum restraint for safe transport.

Sensolite 120

- Laser receiver with head magnet.
- Max. laser reception range 120 m radius.
- High-luminosity LEDs on front and rear.
- Incl. universal mount.

165 cm lightweight aluminium tripod

- Professional model with 5/8" thread.
- Milled bearing surface, durable steel feet.

Flexi levelling staff 210 cm

- For taking measurements from floor heights.
- **Differences in levels determined** without having to carry out any calculations.

TECHNICAL DATA

ACCURACY ± 3 mm / 10 m
SELF-LEVELLING RANGE ± 3,5°
LEVELLING Automatic horizontal / vertical with adjustable foot
LASER RECEPTION RANGE max. 120 m radius
LASER WAVELENGTH 635 nm
LASER class 2, < 1 mW
POWER SUPPLY 6 x type AA, for about 45 operating hours
WATER AND DUST PROTECTION IP 54



Article-No: 046.04.00A

EAN-Code: 4 021563 670598

AquaPro Laser 120 Set

- including AquaPro 120
- + Sensolite 120
- + universal mount
- + 165 cm lightweight aluminium tripod
- + Flexi levelling staff 210 cm
- + soft bag
- + batteries

Packing dimension (B x H x D)
237 x 1181 x 232 mm

PU 2



Vertical operating position

Wall attachment

Compact laser receiver

