

## AutoSmart-Laser 100 Set

Rev.0611



### Automatic rotary laser for indoors and outdoors

#### AutoSmart-Laser

- **Sensor Automatic:** fully automatic alignment via electronic positioning motors controlled by temperature-stable sensors.
- A **vertical reference beam** is provided to plumb and align partition walls.
- **Out-of-level:** The device emits visual signals to indicate that it is out of the levelling range.
- **Transport Lock:** a special motor lock protects the unit during the transport.

#### SensoLite 100

- Laser receiver with head magnet.
- Max. laser reception range 100 m radius.
- High-luminosity LEDs and melodies indicate the level of the laser beam.
- Incl. universal mount.

#### Compact Tripod 150 cm

- Crank tripod of aluminium
- 5/8" thread adapter

#### TECHNICAL DATA

<b>ACCURACY</b> ± 4 mm auf 10 m
<b>SELF-LEVELLING RANGE</b> ± 4°
<b>LEVELLING</b> horizontal and vertical automatic
<b>LASER RECEPTION RANGE</b> max. 100 m radius
<b>LASER MODES</b> spot, scan, rotary and hand receiver mode
<b>LASER WAVELENGTH</b> 635 nm
<b>LASER</b> class 2, < 1 mW
<b>POWER SUPPLY</b> 4 x type AA, for about 12 operating hours
<b>WEIGHT</b> 0,75 kg
<b>DIMENSIONS</b> (W x H x D) 155 x 130 x 150 mm
<b>Laser 635 nm</b> <b>SENSOR AUTOMATIC</b> lock
5/8"              4 x AA



**Article-No: 055.04.00A**

EAN-Code: 4 021563 674992

#### AutoSmart-Laser 100 Set

- inklusive AutoSmart-Laser
- + SensoLite 100
- + universal mount
- + Compact Tripod 150 cm
- + softbags
- + batteries

**Packing dimension** (B x H x D)  
185 x 860 x 175 mm

VE 1



Sensor-Automatic

Vertical operating position

Compact laser receiver

